



MODELO / MODEL		FREEDOM SERIES (Black,Grey,Pearl,Oxide)		
FOTO / PICTURE (orientative)				
FORMATO / SIZE		60 X 120 cms. RECT. / 24" X 48" RECTIFIED		
ACABADO / FINISHING		PULIDO / POLISHED		
GRUPO / GROUP		Bla		
TIPO / TYPE		PORCELANICO ESMALTADO / Glazed Porcelain Tile		
DESCRIPCION DEL TEST / TEST DESCRIPTION		VALOR DEL TEST / TEST VALUE		NORMA / STANDARD
ABSORCIÓN DE AGUA / WATER ABSORPTION		AA ≤ 0,5%	Cumple / Complies	UNE-EN-ISO 10545-3
FUERZA DE ROTURA / BREAKING STRENGTH		≥ 1300 N	Cumple / Complies	UNE-EN-ISO 10545-4
RESISTENCIA A LA FLEXIÓN / RESISTANCE OF FLEXION		≥ 35 N/mm2	Cumple / Complies	UNE-EN-ISO 10545-4
ABRASION SUPERFICIAL / SURFACE ABRASION		Clase / Class	PEI IV	UNE-EN-ISO 10545-7
RESISTENCIA AL CUARTEO / CRACKING RESISTANCE		Requerido / Requested	Cumple / Complies	UNE-EN-ISO 10545-11
RESISTENCIA A LA HELADA / FROST RESISTANCE		Requerido / Requested	Cumple / Complies	UNE-EN-ISO 10545-12
RESISTENCIA QUIMICA / CHEMICAL RESISTANCE	(PRODUCTOS DOMESTICOS Y DE PISCINA / Domestic & Swimming Pool Products)	Mínimo / Minimum GB	Cumple / Complies	UNE-EN-ISO 10545-13
RESISTENCIA A LOS ACIDOS / ACID RESISTANCE		GLA	Cumple / Complies	UNE-EN-ISO 10545-13
RESISTENCIA A LAS BASES / ALKALINE RESISTANCE		GLA	Cumple / Complies	UNE-EN-ISO 10545-13
RESISTENCIA A LAS MANCHAS / RESISTANCE TO STAINS		Mínimo / Minimum Class 3	Cumple / Complies	UNE-EN-ISO 10545-14
RESISTENCIA AL DESLIZAMIENTO / SLIP RESISTANCE		Péndulo / Pendulum	Clase 1 / Class 1	UNE-41901 EX
RESISTENCIA AL DESLIZAMIENTO / SLIP RESISTANCE		D.C.O.F.	> 0.42	ANSI A137. 1:2012. 9.6
RESISTENCIA AL DESLIZAMIENTO / SLIP RESISTANCE		Rampa / Inclined platform	R9	DIN 51130:2014-5
RESISTENCIA AL RAYADO / HARDNESS (MOHS)		Mínimo / Minimum 3	Cumple / Complies	EN-101