


MODELO / MODEL		NAIS SERIES		
FOTO / PICTURE (orientative)		 P.E. NAIS WHITE PUL. 60X120 RECT. PUL.		
FORMATO / SIZE		60 X 120 cms. RECT. / 24" X 48" RECTIFIED		
ACABADO / FINISHING		PULIDO / POLISHED		
GRUPO / GROUP		Bla		
TIPO / TYPE		PORCELANICO ESMALTADO / Glazed Porcelain Tile		
<u>DESCRIPCION DEL TEST / TEST DESCRIPTION</u>		<u>VALOR DEL TEST / TEST VALUE</u>		<u>NORMA / STANDARD</u>
ABSORCIÓN DE AGUA / WATER ABSORPTION		AA ≤ 0,5%	Cumple / Complies	UNE-EN-ISO 10545-3
FUERZA DE ROTURA / BREAKING STRENGTH		≥ 1300 N	Cumple / Complies	UNE-EN-ISO 10545-4
RESISTENCIA A LA FLEXIÓN / RESISTANCE OF FLEXION		≥ 35 N/mm <sup>2</sup>	Cumple / Complies	UNE-EN-ISO 10545-4
ABRASION SUPERFICIAL / SURFACE ABRASION		VALOR DECLARADO / DECLARED VALUE	Clase / Class 4	UNE-EN-ISO 10545-7
RESISTENCIA AL CUARTEO / CRACKING RESISTANCE		Requerido / Requested	Cumple / Complies	UNE-EN-ISO 10545-11
RESISTENCIA A LA HELADA / FROST RESISTANCE		Requerido / Requested	Cumple / Complies	UNE-EN-ISO 10545-12
RESISTENCIA QUIMICA / CHEMICAL RESISTANCE	(PRODUCTOS DOMESTICOS Y DE PISCINA / Domestic & Swimming Pool Products)	Mínimo / Minimum B	Cumple / Complies	UNE-EN-ISO 10545-13
ACIDOS Y BASES A BAJA CONCENTRACION / LOW CONCENTRATION OF ACIDS & ALKALIS		VALOR DECLARADO / DECLARED VALUE	LA	UNE-EN-ISO 10545-13
RESISTENCIA A LAS MANCHAS / RESISTANCE TO STAINS		Mínimo / Minimum Class 3	Cumple / Complies	UNE-EN-ISO 10545-14
RESISTENCIA AL RAYADO / HARDNESS (MOHS)		Mínimo / Minimum 3	Cumple / Complies	EN-101