

DECLARATION OF PERFORMANCE
N°: DoP-F
Rev. 5 – 22/09/2021

1. Unique identification code of the product type:
DRY- PRESSED CERAMIC TILES, WITH WATER ABSORPTION $E_b \leq 0,5\%$
2. Intended uses:
FOR INTERNAL AND EXTERNAL WALLS AND FLOORINGS
3. Name and contact address of the manufacturer:
EMILCERAMICA S.r.l. a socio unico
Via GHIAROLA NUOVA, 29 41042 FIORANO M.SE (MO) ITALY
Tel. : +39 0536 835111 Fax : +39 0536 835306
contact@emilceramicagroup.it www.emilgroup.it
4. System of AVCP: **SYSTEM 4**
5. Name and identification number of notified laboratory: **NOT APPLICABLE**
6. Declared Performances:


ESSENTIAL CHARACTERISTICS	PERFORMANCE		HARMONISED TECHNICAL SPECIFICATION
Reaction to fire	Class A1 _{fl} /A1		EN 14411:2012
Release for dangerous substances, for:	Cadmium	NPD	
	Lead	NPD	
Breaking strength	Thickness $\geq 7,5$ mm	≥ 1300 N	
	Thickness $< 7,5$ mm	≥ 700 N	
Slipperiness	See Annex 1/.....		
Tactility	NPD		
Bond strength/adhesion	NPD		
Thermal Shock Resistance	Pass		
Durability for:			
Internal Uses:	Pass		
External Uses: freeze-thaw resistance	Pass		

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Fiorano M.se (MO)
22/09/2021

Luca Gatti
President



**SLIPPERINESS: ANNEX 1 / LEVEL**

Rev. 3 - 09/2021

		DIN 51130 (DE)	BCRA D.M. 236/1989 (ITA)	UNE 41901:2017 EX (ESP)	CEN/TS 16165 Annex B
TEST METHOD USED		Ramp	Tortus	Pendulum	Ramp (Critical angle α_{shod})
Series	Surface	Value / class			
LEVEL CONCRETE	Naturale	R9	$\geq 0,40$	NPD	≥ 6
LEVEL DESIGN	Naturale	R9	$\geq 0,40$	NPD	≥ 6
LEVEL MARMI	Naturale	R9	$\geq 0,40$	NPD	≥ 6
	Full Lappato - Lappato matt	NPD	NPD	NPD	NPD
LEVEL TINTA UNITA	Naturale	R9	$\geq 0,40$	NPD	≥ 6
	Full Lappato	NPD	NPD	NPD	NPD
LEVEL STONE	Naturale	R9	$\geq 0,40$	NPD	≥ 6